

## How to Use Nitro OBD2 Chip Tuning Box for your car?

### How to Install and Calibrate:

1\* Pull the Car Key out from the ignition.

2\* Find OBD2 connector(\*) in your car and Plug in NitroOBD2 Chip Tuning Box:

**Does your car have OBD2 connector?**

On-Board Diagnostics, or “OBD,” is a computer-based system built into all 1996 and later light-duty vehicles and trucks, as required by the Clean Air Act Amendments of 1990.

OBD systems are designed to monitor the performance of some of an engine’s major components including those responsible for controlling emissions.

**OBD2 necessarily for cars:**

- Sold after January 1, 1996 in the USA
- Sold after January 1, 2001 in the European Union
- With diesel engine sold after January 1, 2003

**Where located OBD2 connector in your car?**

1 Driver’s side, underneath dashboard, in the area under the steering column,

2 Driver’s side, underneath dashboard, between the driver-side door and steering column area

3 Driver’s side, underneath dashboard, between the steering column area and the center console

4 Driver’s side, dashboard instrument/gauge area, between the steering column and center console

5 Driver’s side, dashboard instrument/gauge area, between the driver-side door and steering column

6 Center console, vertical surface left of vehicle centerline

7 Center console, vertical surface right of vehicle centerline or on passenger side of center console

8 Center console, horizontal surface in front passenger area.



**Certificates : CE / FCC / RoHS**

**3\*** Insert the key into the ignition and twist the key to the first stage.  
(Do not start the car)

**4\*** Press the reset button for about 5 sec. After releasing the button, just wait for a while about 30–54 sec. (NitroOBD2 Chip Tuning Box will communicate and establish connection with ECU)

**5\*** Start up the engine.

**6\*** NitroOBD2 Chip Tuning Box will recognize your vehicle and your driving habits, after around 200 km/150 miles driving and thus NitroOBD2 Chip Tuning Box will adjust itself to match your car perfectly for more fuel saving.

Each device available for LPG.

**More attentions:**

1. Plug NitroOBD2 into OBD2 connector of your car. And turn the ignition on for 30 seconds. And Turn the engine on.

2. NitroOBD2 settings are optimal and the best for your car. Even the parameters are different for each vehicle, there might not be a need to make an additional adjustment. NitroOBD2 will recognize your vehicle and your driving habits after around 200 km/150 miles driving, and then NitroOBD2 adjusts itself to match your car perfectly.

3. NitroOBD2 works on the basis of changing the signal from ECU. As a consequence, it changes the whole injection map.

4. The main difference between NitroOBD2 Chip Tuning Box and Remapping tuning methods is that NitroOBD2 Chip Tuning Box is easily removable, and after unplug you go back to the factory settings. EcoOBD2 is the cheap and safe type of tuning.

5. Remapping is a permanent change to your car. This is the expensive tuning and you cannot remove it.

NitroOBD2 is equipped with the engine protection function and 100% safe for your car engine.

NitroOBD2 produced on the printed circuit board in SMD technology.

NitroOBD2 Chip Tuning Boxes are high quality.

Customer feedback on Nitro OBD2 ECU tuning tool Car:

TOYOTA

Review: see clearly see the Vigo accelerator lightly around the sensitive fuel

Car: TOYOTA VIOS

Review: Install this tuning box myself with a cast Vios runs to more than 100 Slovak gas pedal right now. Throttle more light. Very good. shot Oil fell to a little gay. I think this is great.

Car: TOYOTA SUV

Review: Never install a scanner as easy as NitroOBD2 box. Add the instant acceleration and fuel economy.

Plug and Drive NitroOBD2 Performance Chip Tuning Box for Diesel Cars with 2 Year Warranty:



Plug and Drive NitroOBD2 Performance Chip Tuning Box for Benzine Cars:

